



HUSQVARNA LB 155S

Robust and reliable self-propelled mower with high capacity and the option of BioClip® (mulching) and side ejection. The front-wheel drive and the big rear wheels make this mower extra easy to use and manoeuvre. Further features include ergonomic soft-grip handle and robust ball-bearing wheels. The handle also folds down for simplified storage and transport.



BioClip®

The grass is cut into small pieces that quickly decompose and return to the lawn as fertiliser, also making the lawn more drought resistant.



Briggs & Stratton engine

Easy-to-start, powerful Briggs & Stratton engine.

Additional features

- **Comfort handle**
Comfortable handle with easy-access controls.
- **Handle height adjustment**
Adjustable handle height for improved ergonomics.
- **Foldable handle**
For simplified storage and transport.

Technical data

Engine

Engine manufacturer	Briggs & Stratton
Engine name	650EXI
Cylinder displacement	163 cm ³ / 9.95 cu.inch
Net power at preset rpm	2.4 kW @ 2950 rpm
Fuel tank volume	1 lit / 0.26 gal.

Drive system

Drive system	Front wheel drive
Drive wheels	Front
Transmission manufacturer	General Transmission

Cutting deck

Cutting deck material	Steel
Cutting methods	Mulching/Side discharge
Cutting width	55 cm / 22 inch
Cutting height, min-max	33 - 89 mm / 1.3 - 3.5 inch
Cutting height steps	5
Cutting height adjustment	Individual

Equipment

Handle type	Comfort
Wheel bearing, front/rear	Metal bushing/Double ball bearings

Dimensions

Wheel size, front/rear	203 mm/305 mm / 8 inch/12 inch
Length	172.72 cm / 68 "
Width	59.7 cm / 23.5 "
Height	99.06 cm / 39 inch
Weight	33.38 kg / 73.6 lbs

Sound and noise data

Sound pressure level at operators ear	84 dB(A)
Sound power level, measured	98 dB(A)
Sound power level, guaranteed (LWA)	98 dB(A)

Logistics

Packaging size, LxWxH	972.82x642.62x528.32 mm / 38.3x25.3x20.8 inch
Packaging volume	0.33 m ³ / 11.7 cu.feet
Weight packaging	4.99 kg / 11 lbs
Gross weight	39.1 kg / 86.2 lbs

Vibration data

Vibration weighted level	2.5 m/s ²
--------------------------	----------------------