



HUSQVARNA 525PT5S

Designed for professionals, the Husqvarna 525PT5S pole saw with telescopic shaft offers our longest reach, with excellent ergonomics and superior balance to help you achieve high-end results with minimum effort. Easy to manoeuvre, its X-Torq® engine ensures rapid acceleration and high torque with low emissions and low fuel consumption.



Telescopic tube

The tube has a telescopic function for quick cutting height adjustment




Intuitive controls

The choke and purge are easy to reach and understand.

Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



Magnesium clutch housing

Robust magnesium clutch housing for tough professional use, ensuring a long service life.



FEATURES

- Auto return stop switch for easy starting
 - Intuitive controls
 - Telescopic tube for quick cutting height adjustment
- Magnesium clutch housing ensures long service life
 - Rear impact guard
 - Adjustable, automatic chain lubrication

Technical specifications	
DIMENSIONS	
Length, extended, including cutting equipment	402 cm
Length, extended, including cutting equipment	158.3 in
Weight (excl. cutting equipment)	15.43 lbs
Weight (excl. cutting equipment)	7 kg
ENGINE	
Cylinder displacement	1.55 cu.inch
Cylinder displacement	25.4 cm³
Fuel consumption	395 g/kWh
Fuel tank volume	17.25 fl oz
Fuel tank volume	0.51 l
Idling speed	3000 rpm
Maximum power speed	8500 rpm
Power output	1.34 hp
Power output	1 kW
LUBRICANT	
Oil tank volume	0.3 US pint
Oil tank volume	0.14 l
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	107 dB(A)
Sound pressure level at operators ear	89 dB(A)
VIBRATION	
Equivalent vibration level,(ahv, eq), front handle, collapsed	6.3 m/s²
Equivalent vibration level,(ahv, eq), rear handle, collapsed	5.3 m/s²
Equivalent vibration level,(ahv, eq), front handle, extended	4.1 m/s²
Equivalent vibration level,(ahv, eq), rear handle, extended	6.7 m/s²

FREQUENT PARTS



FUEL FILTER FOR MOST OF OUR
HANDHELD PRODUCTS
503 44 32-01

PURGE BUBBLE
503 93 66-01